

Care & Clean

LAMINATE
FLOORING

Preventative measures

- ✓ Sufficiently sized textile clean-off zones of at least 4 to 6 running meters can reduce the amount of dirt brought into a property by up to 80%, significantly influencing the utility value of the flooring and the cleaning costs.
- ✓ firstly, laminate flooring should be cleaned regularly, with the nature and extent of the cleaning depending on the area of application and frequency of use.
- ✓ Cleaning and protective measures during construction: During the construction phase, dust, sand, and any other loose dirt should be removed with a broom or vacuum cleaner. Once laid, the surface should be protected with a suitable cover during subsequent interior construction work.
- ✓ Following the installation process, the floor covering must be protected against damage via suitable protective covers in areas that are regularly frequented during the construction phase. Moisture trapped under items of furniture must be avoided.
- ✓ Chairs, tables, and furniture legs must be protected with suitable protector pads or underlay.
- ✓ Chair castors as well as chair and furniture gliders must be regularly maintained. Contact areas of chair and furniture gliders must lie completely flat and be rounded at the edges. Metal gliders can corrode when exposed to moisture and cause stains.
- ✓ In the case of underfloor heating, the temperature of the surface covering must not persistently exceed 27 °C. This also applies if there is a carpet on top – trapped heat poses a danger!

Initial treatment

- ✓ The surface does not require a protective film. Film-forming care products are prohibited as they impair the use and make the surfaces harder to clean.

Everyday cleaning

- ✓ Clean the floor with a brush or vacuum cleaner to remove loose dust and dirt. Vacuuming is generally sufficient for everyday cleaning purposes. For more thorough everyday cleaning, we recommend using a cleaning agent such as Laminate cleaner or similar products. Please observe the instructions of the care product manufacturer!
- ✓ When carrying out wet cleaning, please use water and cleaning agents sparingly (wipe with a damp cloth). Do not use any abrasive microfibers (scratching/scraping) to wipe the surface. Do not use film-forming cleaning agents.

General notes:

- ✓ The compatibility of adhesive tape with laminate floor coverings should be checked in advance with the relevant manufacturer or the user of the floor covering.
- ✓ The non-slip properties and safe-footing characteristics of floor coverings are significantly influenced by the application of dirt, cleaning frequency, and the cleaning/maintenance products used.
- ✓ Please only use coordinated cleaning and maintenance products from one manufacturer. Abrasive cleaning powders, sanitary cleaners, acids, and strong solvents can damage the covering surface or items of furniture.
- ✓ It is not possible, however, to rule out the possibility of fading/changes in color in areas exposed to strong UV light on a long-term basis. Sufficiently sized shades can be used to minimize or prevent fading and changes in color.
- ✓ Pigmented wound and hand disinfectants as well as hair dye or bleaching agents containing peroxide can cause irreversible discoloration. If you are unsure about using chemical coloring substances or food products, you should carry out a resistance test on an inconspicuous part of the flooring or on a not-yet-installed piece first.
- ✓ No use of steam mop.

Please observe the instructions of the care product manufacturer!