Care and Clean



Wax oiled Care and Clean

- ✓ All Wax oiled floors should be thoroughly cleaned right after installation and as part of a regular cleaning regime. The surface will then be more hardwearing and easier to clean and maintain in the future.
- This is because the recommended soap used to clean oiled floors coats the surface with an invisible film, providing additional protection and making the floor more resistant to dirt.
- Simply use a brush or vacuum cleaner for normal cleaning to remove surface debris. In order to achieve the best cleaning possible, use an oiled flooring soap cleaner. This highly concentrated soap is for cleaning and maintenance of oiled wooden surfaces, suitable for flooring, furniture, kitchen surfaces, and all indoor wood.
- ✓ Do not wipe the floor with pure water after using the soap as the protective oils will be removed!

Use a flooring refresher once or twice a year, depending on the level of dirt, to restore and protect if the floor has become dull and tired looking. It will help in everyday care, reinforce the floor's resistance to dirt, and give your floor a new lease of life.

- ✓ First, clean the soiled surface with Wax Oiled Flooring Intensive Cleaner, and leave to dry thoroughly for 4 to 8 hours.
- Apply a thin layer of Easy Clean Oiled Flooring Refresher with a diffuser or a cloth and then rub it into the wood until a smooth, silky-matt surface is revealed.
- ✓ Make sure you leave no excess oil on the surface.
- Within approx. 4 hrs. The floor may be walked on, though the full hardening time is 24 hrs. During this time the floor must not be cleaned with water and should be used sparingly and with care.

Wax oiled maintenance, care, and cleaning tips:

- ✓ Spills and tracked-in dirt should be wiped up right away.
- Sweep, dust, or vacuum using a hard floor attachment once a week or more if needed. Do not use vacuums with beater bars or hard heads.
- ✓ Clean with a recommended cleaning product made for Hardwood Flooring wax oiled as needed.
- ✓ Don't allow liquids to stand on your floor.
- ✓ Never use buffing machines as they can damage your Hardwood Flooring.
- Steel wool or scouring powder is abrasive and will damage your floor's finish.
- Steam mops may cause damage to Hardwood Flooring due to the high temperature of the steam. do not steam mops.

Stain and Spot Removal Tips:

- ✓ Wet spills should be wiped up immediately.
- ✓ A warm, damp cloth can be used to wipe up the substance from your floor.
- Use a cleanser made for Hardwood Flooring to help clean more stubborn soil.
- For sticky substances, harden the spot with an ice cube and lightly rub it with a dull plastic scraper. Do not apply too much pressure as this could damage or scrape the floor's finish.

Note: After the floor installation is completed, do not place coverings on the floor within 6 months, as this may cause discoloration of the floor. If it is necessary to use coverings, please move them frequently.

Please observe the instructions of the Wax oiled care and clean product manufacturer!

Lacquer Care and Clean

✓ Normal cleaning to remove surface debris is accomplished using a broom or vacuum cleaner. To remove normal stains and dirt, the floor should be cleaned with a lacquered floor cleaning spray. Simply spray evenly across the floor, allow a minute to work on any stubborn marks, and simply mop over.

Lacquered maintenance, care, and cleaning tips:

- ✓ Spills and tracked-in dirt should be wiped up right away.
- Sweep, dust, or vacuum using a hard floor attachment once a week or more if needed. Do not use vacuums with beater bars or hard heads.
- ✓ Don't allow liquids to stand on your floor for over 24 hours.
- ✓ Never use buffing machines as they can damage your Hardwood Flooring.
- Steel wool or scouring powder is abrasive and will damage your floor's finish.
- Steam mops may cause damage to Hardwood Flooring due to the high temperature of the steam. do not steam mops.

Stain and Spot Removal Tips:

- ✓ Wet spills should be wiped up immediately.
- ✓ A warm, damp cloth can be used to wipe up the substance from your floor.
- Use a cleanser made for Hardwood Flooring to help clean more stubborn soil.
- For sticky substances, harden the spot with an ice cube and lightly rub it with a dull plastic scraper. Do not apply too much pressure as this could damage or scrape the floor's finish.

Note: After the floor installation is completed, do not place coverings on the floor within 6 months, as this may cause discoloration of the floor. If it is necessary to use coverings, please move them frequently.

Please observe the instructions of the Lacquer care and clean product manufacturer!